Contents:

Part I
Chapter 1 The Problem Imposed by Racing
Chapter 2 Tire Behavior 13 2.1 Lateral Force 15 2.2 Aligning Torque and Pneumatic Trail 28 2.3 Longitudinal Force 32 2.4 Combined Operation 41 2.5 Camber Effects 46 2.6 Other Tire Effects 54 2.7 Friction Circle and Ellipse 57 2.8 SAE Tire Axis System 61 2.9 Discussion of Tire Forces 63 2.10 Discussion of Tire Moments 69 2.11 Torque About the Wheel Spin Axis 74 2.12 Goodyear Tire Data 75
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Chapter 4 Vehicle Axis Systems1134.1 Two Types of Axis Systems1144.2 Vehicle Motions1174.3 Some Thoughts on Sign Conventions1194.4 Symbol Conventions in this Book121
Chapter 5 Simplified Steady-State Stability and Control1235.1 Approach1245.2 The Elementary Automobile Defined1265.3 Steady-State Low-Speed Cornering Geometry128

5.4 Steady-State Cornering of the Neutral Steer Car	129
5.5 Steady-State Cornering of the Understeer Car	135
5.6 Steady-State Cornering of the Oversteer Car	140
5.7 Equations of Motion	144
5.8 Physical Significance of the Derivatives	151
5.9 Steady-State Responses	153
5.10 Neutral Steer Responses	157
5.11 Understeer and Oversteer Responses	160
5.12 Significant Speeds	174
5.13 Static Stability and Control	191
5.14 Steady-State Path Curvature Stiffness	201
5.15 Steady-State Response Data	210
5.16 Steady-State Nonlinear Analysis	219
5.17 General Conclusions on Steady-State	224
Chapter 6 Simplified Transient Stability and Control	231
6.1 Approach	232
6.2 The Spring-Mass-Damper System	
6.3 Dynamic Stability—Two-Degree-of-Freedom Automobile	241
6.4 Single-Degree-of-Freedom Analysis	245
6.5 Two-Degree-of-Freedom Normalized Response Charts	
6.6 Notes on Stability Derivative Concept	260
6.7 Transient Response Data	
6.8 Early Analytical Approach	266
6.9 Advanced Vehicle Dynamics Models	272
Chantan 7. Chan In Chan B. 'a A a 1. '	0.70
Chapter 7 Steady-State Pair Analysis	279
7.1 Pair Analysis Procedure	283
7.2 MRA Computer Program	
7.3 Example Calculations	
7.4 Lateral Load Transfer—Discussion	289
Chapter 8 Force - Moment Analysis	293
8.1 Approach	294
8.2 Constrained Testing	294
8.3 Computer Program	297
8.4 Moment Method Results	301
8.5 Limit Behavior	313
8.6 N-A _Y , Race Car Example	319
8.7 C _N -A _Y , Sports Car Chassis Tuning Example	327
8.8 Lap Time Analysis	340
Chapter 9 "g-g" Diagram	345
9.1 Conceptual Development	345
9.2 General Uses	3/18

9.4 Race Car Applications	350 354 359
10.1 Constraints and Specification	367 368 369
11.1 Driver-Vehicle Relationship 11.2 Desirable Vehicle Characteristics 11.3 Fundamentals of Testing 11.4 Track Test Program Planning 11.5 Test Methodology 11.6 Some General Notes on Development	373 374 375 376 378 378 381 383
12.1 Set-up	387 388 391 401
Chapter 13 Historical Note on Vehicle Dynamics Development	413
Part II	
14.1 Tire Data Nondimensionalization	473 474 475 480 484
15.1 Historical Note on Aerodynamic (Lift) Downforce	489 490 492 496 511 521 528 536 546 555 560

15.11 Miscellaneous	
Chapter 16 Ride and Roll Rates 16.1 Definitions 16.2 First Example with More Complete Calculations 16.3 Installation Ratios 16.4 Finishing the First Example Case 16.5 Second Example with Simplified Calculations	595
Chapter 17 Suspension Geometry 17.1 Degrees of Freedom and Motion Path 17.2 Instant Center Defined 17.3 Independent Suspensions 17.4 Beam Type Axle Suspensions 17.5 Front Suspensions 17.6 Independent Rear Suspensions 17.7 Beam Axle Rear Suspensions 17.8 Twist Axle Rear Suspensions	607 608 610 612 621 624 636 647 661
Chapter 18 Wheel Loads 18.1 Assumptions Used in this Chapter 18.2 Center of Gravity Location 18.3 Chassis Stiffness 18.4 Lateral Load Transfer 18.5 Longitudinal Weight Transfer 18.6 The Effects of Banking 18.7 Other Terrain Effects 18.8 Aerodynamic Loads 18.9 Engine Torque Reaction 18.10 Asymmetrical Effects 18.11 Summary Example	665 665 666 673 678 684 685 690 694 697 700 704
Chapter 19 Steering Systems 19.1 Steering Geometry 19.2 Ackermann Steering Geometry 19.3 Steering Gears 19.4 Ride and Roll Steer 19.5 Alignment	709 709 713 716 721 726
Chapter 20 Driving and Braking 20.1 Merits of Front-, Rear-, and Four-Wheel Drive 20.2 Differentials 20.3 Brake Systems	729 729 733 749

Chapter 21 Suspension Springs 21.1 Torsion Springs 21.2 Coil Springs 21.3 Coil Springs in Series and Parallel 21.4 Coil Spring Calculations 21.5 Leaf Springs 21.6 Leaf Spring Installation Considerations 21.7 Fatigue	755 755 762 766 770 771 775 777
Chapter 22 Dampers (Shock Absorbers) 22.1 Approach 22.2 Technical Literature 22.3 Damping Fundamentals 22.4 Racing Application 22.5 Race Cars with Modest Aerodynamic Downforce 22.6 Race Cars with Aerodynamics Critically Affected by Ride Height and Pitch	781 783 783 786 810 820
Chapter 23 Compliances	833
References	841
Index	857

Figures

1.1 1.2 1.3 1.4 1.5	Circuit simulation results	5 6
2.1 2.2 2.3 2.4 2.5 2.6 2.7	Mechanism of tire lateral force in elastic range	16 17 19 21 23 24 25
2.8 2.9	Lateral force vs. slip angle for several loads	26 27
2.10 2.11 2.12	Aligning torque vs. slip angle for several loads	29 30 31
2.13 2.14	Tire print characteristics—driving (Ref. 33)	33 34
2.15 2.16 2.17	Typical traction—slip ratio curve; slip angle = 0°	36 38 38
2.17 2.18 2.19	Braking and traction forces vs. slip ratio and slip angle (Ref. 136)	42 42
2.20 2.21	Effect of slip angle and slip ratio on lateral force	43 44
2.22	Distortion in print of a tire at a camber angle	45 47
2.24 2.25 2.26	Peak side force vs. camber (Ref. 46)	48 49 49
2.27 2.28	•	51 52
2.29 2.30 2.31 2.32 2.33	Lateral force at 10° camber, lean to right for LH front wheel Load sensitivity for several camber angles	53 54 58 61 62
2.34	Components of the net rolling resistance, F _R	65

2.35	Tire resistance due to slip angle and input torque (Ref. 55)	66
2.36	Lateral force induced drag—cornering vehicle	67
2.37	Aligning torque	70
2.38	Tire overturning moment	70
2.39	Free-rolling tire	72
2.40	Rolling resistance torque	73
2.41	Rolling resistance moment as a function of load	74
2.42	Goodyear data—Eagle GT-S	76
2.43	Goodyear data—Short Track Stock	77
2.44	Goodyear data—Eagle ZR	78
2.45	Goodyear data—Indy Car road course rear	79
2.46	Goodyear data—F.1 front	80
3.1	Static pressure tube, for measuring p in free stream	91
3.2	Static pressure tap, for measuring p along a surface	91
3.3	Dynamic or "stop" pressure, "q"	92
3.4	Total pressure tap, to measure "H"	93
3.5	Weather vane, left, and Kiel tube, right, for measuring total pressure	94
3.6	Pitot-static tube airspeed indicator	95
3.7	Pressure distribution around a wing	96
3.8	Critical behavior of a hatchback automobile (Ref. 70)	98
3.9	Turbulent wake formation (Ref. 79)	99
3.10		100
3.11	•	100
3.12	Tufts on a wing (Ref. 119)	104
3.13		105
3.14		106
3.15	SAE Aerodynamic Axis System (Ref. 2)	109
	• • •	
4.1	Axis systems used in determination of the vehicle axis system	
	(Ref. 111)	115
4.2		116
4.3	Heading, sideslip, course, and steer angles (Ref. 1)	118
5.1		124
5.2		127
5.3	2 110 110 110 110 110 110 110 110 110 11	128
5.4	Ackermann, parallel, and reverse Ackermann steering	129
5.5	Turning with lateral forces	131
5.6	Research vehicle, constant radius test	132
5.7	Variation of slip angles with lateral acceleration (NS)	133
5.8	NS car on a tilted road	134
5.9	Turning with lateral forces, US car	136
5.10	Turning with lateral forces, US car, $\delta = \delta_{Ackermann}$ (for NS)	138
5.11	Constant radius test for US car	139

5.12	Turning with lateral forces, OS car	141
5.13	Turning with lateral forces, OS car, $\delta = \delta_{Ackermann}$ (for NS)	142
5.14	Steer behaviors on tilted road	143
5.15	Acceleration components in a transient	147
5.16	Velocities at rear tire	147
5.17	Velocities at front tire	148
5.18	The understeer/oversteer spring	152
5.19	Path curvature response (Ref. 92)	163
5.20	Yawing velocity response (Ref. 92)	163
5.21	Neutral steer point	166
5.22	Under/oversteer representation of vehicle stability (Olley)	169
5.23	US speed relationships	178
5.24	Critical speed relationships	179
5.25	Ackermann term, constant throttle test	182
5.26	Slip angle difference term	182
5.27	Simple 2DF car, moment components	183
5.28	Yaw velocity response to control	184
5.29	Minimizing $f = 1/V + KV \dots$	185
5.30	Tire lateral velocity and side force	186
5.31	Tire damper side force—2DF automobile	187
5.32	The damping-in-sideslip	188
5.33	Damping-in-yaw	189
5.34	Trim and stability	193
5.35	NS car directionally disturbed	195
5.36	US car directionally disturbed	196
5.37	Static stability curve for US car	196
5.38	OS car directionally disturbed	197
5.39	Static directional stability	198
5.40	Motions of cars following a disturbance in vehicle slip angle	199
5.41	Steering control moment	200
5.42	Static stability and control, US car, constant speed	201
5.43	Slip angles induced by path curvature, vehicle at $\beta = \delta = 0 \dots$	202
5.44	Yaw moment due to Ackermann steer angle	203
5.45	Path curvature stiffness and yaw damping	203
5.46	Static stability, control, and yaw damping	205
5.47	Stability plot: C_N - A_Y with constant V and constant δ	207
5.48	Stability plot: C_{N} - A_{Y} ; $\delta = 0$; neutral steer car	208
5.49	Stability plot: $C_{N}^{-}A_{Y}$; $\delta = 0$; understeer car	209
5.50	Stability plot: C_N - A_Y ; $\delta = 0$; oversteer car	210
5.51	Steady-state response tests	213
5.52	Steering sensitivity vs. speed	216
5.53	Steady-state steer test and "understeer" gradient	217
5.54	Steering sensitivity vs. lateral acceleration, steady-state test	218
5.55	Path radius, R, vs. total input thrust, T	220

5.56	Plan view of vehicle showing responses and tire forces ($\delta = 8^{\circ}$)	222
5.57	Plot of vehicle responses vs. driving thrust	223
6.1	Spring-mass-damper system	234
6.2	Another SMD system	235
6.3	Effect of damping ratio on transient response	
	of spring-mass-damper system	238
6.4	"Quarter-car" SMD system	239
6.5	Transient sideslip response to side force, $F_v(r=0)$	247
6.6	Yawing motion definitions	248
6.7	Normalized responses, $\omega_n \tau = 0.5 \dots$	252
6.8	Normalized responses, $\omega_n \tau = 1.0$	252
6.9	Response time, underdamped case	253
6.10	Response time, overdamped case	253
6.11	Time to peak response	254
6.12	Percent overshoot	255
6.13	Rise time and peak response time (Ref. 9)	261
6.14	Transient response to ramp steer inputs, $V = 62 \text{ mph} \dots$	262
6.15	Yaw velocity / lateral acceleration rise times,	
	from straight path, 62 mph	263
6.16	Yaw velocity / lateral acceleration rise times,	
	from curved path, 62 mph	264
6.17	Typical free control data records	265
6.18	Effect of front- and rear-wheel driving thrust on steady	
	turning at low speed	266
6.19	Effect of front- and rear-wheel driving thrust on step	
	steer response	268
6.20	Neutralizing steering on "spin" recovery, rear-wheel	
	driving thrust = 500 lb	269
6.21	"Spin" recovery by simulated "driver" at low speed	270
6.22	"Spin" recovery by simulated "driver" at higher speed	271
6.23	VDS correlation—1	275
6.24	VDS correlation—2	276
7.1	Wheel pair on a single track	284
7.2	Ackermann steer, 0° camber, 0° toe	286
7.3	Axle pair analysis—1	290
7.4	Axle pair analysis—2	291
7.5	Reverse Ackermann steer, -15° camber, 1° toe-out/wheel	292
	,	
8.1	Constrained model on moving belt	295
8.2	Constrained proving ground tests on automobiles	298
8.3	Full-scale test devices for making MMM measurements	300
8.4	Cornering force curves for model tires	302
8.5	Build up of C _N -C _Y MMM example	303

8.6	C _N -C _Y example, right-hand turn, RL power	304
8.7	Typical four quadrant MMM diagram	307
8.8	Lateral force vs. slip angle for a racing tire	314
8.9	Idealized cornering force curve	316
8.10	Cornering forces for the front and rear tracks	317
8.11	Force-moment envelopes	318
8.12	Chaparral, condition #1	321
8.13	Chaparral, condition #2	322
8.14	Chaparral, condition #3	323
8.15	Chaparral, condition #4	324
8.16	Chaparral, condition #5	325
8.17	Chaparral, condition #6	326
8.18	Sports car, baseline	328
8.19	Roll angle vs. A _Y	329
8.20	Steer angle response	330
8.21	Stability index	331
8.22	Trimmed sideslip angle response	331
8.23	Understeer gradient	332
8.24	GM steering sensitivity	332
8.25	Friction circles, baseline	333
8.26	Baseline, rescaled to show peak	334
8.27	MMM parameter study results	337
8.28	MMM study, near-limit friction circles	338
8.29	Formula 1 car performance envelope, c. 1971	342
8.30	Formula 1 performance profile on Watkins Glen fourth circuit	342
	•	
9.1	RWD, braking and D.T	347
9.2	Maneuvering performance of different drivers	349
9.3	On-road maneuvering (typical driver)	349
9.4	Vehicle "g-g" estimates	351
9.5	"g-g" diagram, rear-wheel drive	352
9.6	"g-g" diagram, front-wheel drive	353
9.7	Adelade, 1987, Senna	355
9.8	Silverstone, 1993, Herbert	356
9.9	Belle Isle, 1992, LTS calculations	357
9.10	Belle Isle, speed segregated (lower speeds)	358
9.11	Belle Isle, speed segregated (higher speed)	359
9.12	Silverstone, 1993, Herbert	360
9.13	Longitudinal force vs. side force and torque (Ref. 47)	361
9.14	Corvette "g-g" diagram, 1958	362
9.15		
9.13	"g-g" diagrams from Isuzu, c.1970 (Ref. 108)	365
9.16	"g-g" diagrams from Isuzu, c.1970 (Ref. 108)	365 366
	"g-g" diagrams from Isuzu, c.1970 (Ref. 108)	

13.1	Bill Milliken and Type 35 Bugatti	414
13.2	Maurice Olley	416
13.3	Leonard Segel	423
13.4	Air Force—CAL six component tire test rig	428
13.5	Dave Whitcomb	429
13.6	Cover of "The IME Papers"	430
13.7	Bob Schilling and Joe Bidwell	432
13.8	Frank Winchell, Jim Hall, Jim Musser. STV at Midland with front	
	and rear wings, 1964. Bill Milliken, Frank Winchell, Hap Sharp,	
	Jim Hall at Watkins Glen	440
13.9	Ray McHenry and the Spiral Jump	458
13.10	King Bird and TIRF	461
13.11	Roy Rice, Fred Dell'Amico, and Doug Roland	464
13.12	MTS Flat-Trac Roadway Simulator	466
13.13	Peter Wright and David Williams	467
13.14	CAL, February 5, 1954. Dr. W. Kamm, Bill Milliken, Bob Schilling,	
	Ed Dye, Dave Whitcomb, W. Cyrus, Cliff Nuthall, Len Segel,	
	Bill Close, Ernie DeFusco, Al Fonda	470
14.1	Normalized lateral force, 0° camber	477
14.2	Normalized self-aligning torque, 0° camber	477
14.3	Normalized camber thrust, 0° slip angle	478
14.4	Normalized longitudinal force, 0° slip angle	480
14.5	Normalized lateral force at 1800 lb. load	481
14.6	Normalized lateral force at –6° camber	482
14.7	Normalized resultant force vs. normalized slip variable	484
14.8	Lateral force vs. braking force, constant slip angles	485
14.9	Lateral vs. longitudinal force, constant slip angles	485
15.1	Rear spoiler on G.T. car (Ref. 143)	493
15.2	Rear spoiler G.T. car, effect of yaw angle (Ref. 143)	494
15.3	Effect of rear deck lip height on a notchback sedan (Ref. 140)	495
15.4	Front spoiler position—aerodynamics of Charger Daytona	
	front end (Ref. 86)	497
15.5	Front and rear axle lift vs. speed and aerodynamic aids	
	(Ref. 63)	498
15.6	Chaparral G.S. 2G with high-mounted, two-position wing	499
15.7	NACA 0008 airfoil data (Ref. 14)	500
15.8	Airfoil characteristics corrected to Chaparral wing aspect ratio	
	(Ref. 14)	501
15.9	G.S. 2G total resistance from coastdown tests at Midland	503
15.10	Changes in wheel load due to wing drag	504
15.11	G.S. 2G full-scale pressure measurements, unpublished	504
15.12	G.S. 2G aerodynamic downforce	505
15.13	Acceleration, G.S. 2G WOT	506

15.14	Deceleration, G.S. 2G	507
15.15	Firestone 10.50 × 16, 10" rim, 30 psi	509
15.16	Firestone 6.00/13.50 × 15, 13" rim, 30 psi	510
15.17	Negative-lift wing integrated with the body shape	512
15.18	Multiple slotted airfoil (Ref. 165)	512
15.19	Effect of flaps and slats on airfoil lift characteristics (Ref. 61)	513
15.20	High-lift devices (Ref. 61)	514
15.21	Effective aspect ratio of wings as a function of end plate height ratio	
	(Ref. 61)	514
15.22	Rear wing effect on vehicle lift and drag (Ref. 75)	516
15.23	Spanwise load distribution of the rear wing (Ref. 75)	517
15.24	Front wing data (Ref. 75)	518
15.25	Two-dimensional airfoil shapes and computed lift coefficients	
	(Ref. 76)	519
15.26	Modeling of three-dimensional airfoil shapes (Ref. 76)	520
15.27	Historical development of negative lift (Ref. 168)	522
15.28	C _L vs. incidence, symmetrical nose, effect of ground (Ref. 155)	523
15.29	Lotus ground-effects wind tunnel results (Ref. 168)	524
15.30	Simple ground-effects vehicle	525
15.31	Lift, drag, and pitching moment near fixed ground board (Ref. 49)	529
15.32	Sketches of flow with lee side vortices (Ref. 49)	529
15.33	Body with wheels and rough underbody (Ref. 49)	530
15.34	Tests with and without moving belt (Ref. 49)	530
15.35	Venturi test configurations (Ref. 50)	531
15.36	Flow with vortex formation under venturi model (Ref. 50)	532
15.37	Static pressure distribution (Ref. 50)	533
15.38	View of the underbody channels (Ref. 77)	533
15.39	Vortices inside the underbody channels (Ref. 77)	534
15.40	Effect of rear wing (Ref. 77)	535
15.41	Effect of wings on underbody pressure distribution, CART car	
	(Ref. 76)	536
15.42	March F.1 aero features (Ref. 160)	537
15.43	Penske PC-18	537
15.44	Types of airflow in boundary layer, two-dimensional flow	539
15.45	Induced drag, three-dimensional wing	540
15.46	Idealized flow field around a fastback car, schematic (Ref. 65)	540
15.47	VW basic aerodynamic flow body (Ref. 26)	542
15.48	Morelli basic body shape (Ref. 97)	542
15.49	Goldenrod land speed record car (Ref. 80)	543
15.50	Comparison of computed drag forces with experimental values	
	(Ref. 75)	544
15.51	Probe IV body surface nomenclature (Ref. 137)	544
15.52	Fence on wing to prohibit spanwise flow	547
15.53	Guide vanes	548
15.54	Fence on McLaren CanAm car (side of nose)	548

15.55	Vortex structure on rear of a car (Ref. 63)	550
15.56	Trapped vortex produced by cusp on rear body top	
	(see also Ref. 36)	550
15.57	Vortex generator	551
15.58	Use of diffuser and contractor in radiator air duct	552
15.59	Gurney Lip installed on slotted T.E. flap (Ref. 149)	553
15.60	Rao slot and L.E. cuff (Ref. 39)	554
15.61	Fillet at wing/fuselage juncture	554
15.62	Ideal ram air ducted radiator	557
15.63	Simple cooling system model (Ref. 106)	558
15.64	Efficient diffuser / plenum (Ref. 149)	559
15.65	NACA inlet duct (Ref. 23)	561
15.66	Large sideboards	562
15.67	Flat plate drag (Ref. 62)	562
15.68	Drag coefficients of rectangular flat plate (Ref. 62)	563
15.69	C_L and C_D for a flat plate, $AR = 6$ (Ref. 71)	563
15.70	Normal force coefficient of square or circular plates (Ref. 62)	564
15.71	Flat plate axes	564
15.72	Permissible grain diameter to maintain min. surface drag (Ref. 78)	566
15.73	Relative drag of protuberances and gaps (Ref. 78)	567
15.74	Wake patterns—isolated wheel (Ref. 34)	568
15.75	Pressure distributions beneath wheel (Ref. 34)	569
15.76	Pressure distributions around front and rear wheels (Ref. 153)	571
15.77	Tire load sensitivity	574
15.78	F _Y and CF vs. V	576
15.79	Velocity vs. path radius	577
16.1	Ride natural frequency vs. static wheel deflection	583
16.2	Installation ratio for a simple suspension	595
16.3	Installation ratio as a function of ride travel	597
1.07 4		
17.1	Degrees of freedom and suspension motion definitions (Ref. 1)	608
17.2	Kinematics—all independent suspensions have five links	609
17.3	Kinematics—independent wheel motion	610
17.4	Kinematics—axle suspensions have four links	611
17.5	Instant center concept	611
17.6	Kinematics—instant axis concept	613
17.7	Roll center construction	614
17.8	Jacking effect with a high roll center	615
17.9	Camber change	615
17.10	Scrub is a function of IC height	616
17.11	Wheel path on rough road with a large amount of scrub	616
17.12	Derivation of braking anti features with outboard brakes	617
17.13	Braking anti features with inboard brakes	618
17.14	Front-wheel-drive anti-lift (or pro-lift)	619

17.15	Rear anti-squat, (a) solid axle and (b) independent rear suspension	619
17.16	Lateral restraint devices	623
17.17	Front suspension packaging	625
17.18	SLA front view geometry	628
17.19	SLA side view geometry	629
17.20	SLA control arm inner-pivot-axis layout	631
17.21	Choice of instant axis determines the control arm planes	632
17.22	MacPherson strut layout	633
17.23	MacPherson strut spring location to minimize bending	635
17.24	Trailing arm rear suspension	637
17.25	Semi-trailing arm rear suspension	637
17.26	Swing axle rear suspension	638
17.27	Pre-84 Corvette rear suspension	639
17.28	Rear strut suspensions—I	641
17.29	Rear strut suspensions—II	642
17.30	SLA rear suspension—double A-arm and toe link	643
17.31	SLA suspensions—upper A-arm with three links	644
17.32	Thunderbird rear suspension—H-arm and camber link	645
17.33	SLA suspensions—five-link Mercedes type	646
17.34	SLA suspensions—five-link Corvette type	646
17.35	Basic four bar link axle suspension	648
17.36	Parallel lower arm four bar link	650
17.37	A-arm and links axle suspension	651
17.38	Three-link and track bar (Panhard bar)	653
17.39	Torque tube rear axle	655
17.40	"NASCAR" type rear axle	656
17.41	Torque arm rear axle suspension	657
17.42	Decoupled rear axle suspension	659
17.43	Mercedes W125 de Dion rear axle suspension (Ref. 29)	660
17.44	Hotchkiss rear axle (leaf springs)	662
17.45	Twist axle types	663
		cer
18.1	Horizontal location of total vehicle center of gravity	667
18.2	Vertical location of the center of gravity	669
18.3	Lateral and longitudinal sprung mass CG location	671
18.4	Sprung mass center of gravity height	673
18.5	Chassis assembly set up for torsional stiffness testing (Ref. 118)	674
18.6	Bending and torsional stiffness plotted along the length of the	675
	chassis (Ref. 118)	
18.7	Stiffening up tubing joints in bending (Ref. 164)	677
18.8	Total lateral load transfer	678 681
18.9	Lateral load transfer geometry	685
18.10	Longitudinal weight transfer—driving	686
18.11	Banked RH turn, looking forward	
18.12	Effect of grade	691

18.13 18.14 18.15	Effect of crests	693 698 703
19.1 19.2 19.3 19.4	Kingpin geometry	710 714 714
19.5 19.6 19.7 19.8 19.9	forward and backward	715 717 722 723 724 725
20.1	Differential wheel speed, low-speed turning	735
20.2	Open differentials and lever analogy to differential gear action (Ref. 99)	736
20.3 20.4 20.5 20.6 20.7 20.8 20.9 20.10 20.11	Open differential characteristics Planetary, unequal torque differential Locked axle characteristic (spool) Dana Trac-Loc® limited-slip differential Dana Trac-Loc® characteristics Salisbury axle (from ZF) Torsen® all-gear limited-slip differential Torsen II® all-gear limited-slip differential Ferguson Formula viscous differential with planetary differential for 4WD center-box use	737 738 739 741 742 743 744 745
20.12	Ferguson Formula viscous differential characteristics	747
21.1 21.2 21.3 21.4 21.5 21.6 21.7 21.8 21.9 21.10 21.11	Basic geometry of a torsion spring Maximum stress per unit applied torque, k, vs. bar area. Helical coil compression springs (Ref. 6) Springs in series. Two springs in series, (a) no bottoming and (b) one bottoming Springs in series—general case. Springs in parallel Coil spring rate test Leaf springs (Ref. 12) Shackle angle effect on spring rate Estimating fatigue life of steel leaf springs	756 758 762 766 767 768 769 772 773 775
	(preset / not shot peened) (Ref. 5)	778

22.1	Damped spring and mass system	787
22.2	Time histories showing different levels of damping ratio,	
	$\zeta = 0.1 \text{ to } 1.2 \dots$	789
22.3	Simple "one corner" ride model	790
22.4	Vertical accelerations on simple "one corner" ride model	790
22.5	"One corner" ride model including unsprung mass and tire spring	791
22.6	Vertical accelerations on "one corner" ride model of Figure 22.5	791
22.7	Transmissibility of unsprung mass	792
22.8	Ride model including seat flexibility	793
22.9	Passenger acceleration, including seat flexibility	793
22.10	Passenger acceleration vs. damping ratio, ζ	794
22.11	Figure 22.10, with wheel transmissibility	794
22.12	Conventional suspension pitch and bounce centers	795
22.13	Time history of Figure 22.12 (upper part)	796
22.14	Time history of Figure 22.12 (lower part)	796
22.15	Ride comparison in frequency domain	797
22.16	Ride model including damper end rubber isolators	798
22.17	Effects of damper relaxation spring, k _C (carpet plot)	799
22.18	Simple damper characteristics	800
22.19	Damper characteristic showing bump-rebound force ratio	800
22.20	Damper characteristic including orifice effects and "dry" friction	801
22.21	Bump and rebound both plotted in the first quadrant	802
22.22	Damper characteristic with high velocity roll-off	802
22.23	Damper constructions	804
22.24	Damper characteristic, force vs. deflection, classical measurement	805
22.25	Damper characteristic, single loop of the classical measurement	805
22.26	Damper characteristic, replotted against velocity	806
22.27	Effects of damper relaxation spring, 1000 lb./in	807
22.28	Effects of damper relaxation spring, 500 lb./in	808
22.29	Effects of damper relaxation spring, 250 lb./in	809
22.30	DR vs. ride and road-holding performance, compact passenger car	812
22.31	Definitions of tire-ground contact and load fluctuation rates	812
22.32	Load fluctuation and body acceleration, smooth road	813
22.33	Load fluctuation and body acceleration, rough road	813
22.34	Loss of lateral force due to wheel load fluctuation	814
22.35	Steady-state cornering on smooth and good (average) road surface	815
22.36	Steady-state cornering with damper degradation	816
22.37	Steady-state cornering on uneven roadways	816
22.38	Transient maneuver with standard damper	818
22.39	Transient maneuver with twice standard damper	819
22.40	KONI "Graph A"	822
22.41	Transient response as a function of damping ratio, DR	827
22.42	Penske oval track dampers	830
22.43	Penske road course dampers	831
		003

23.1	Lateral force application (Ref. 109)	837
23.2	Lateral force compliance test data (Ref. 109)	838

Fables

	Goodyear Data, Tread Compound Durometer Readings	
5.2 5.3 5.4	Terminology Used in Equations of Motion The Derivatives (Simple Two-Degree-of-Freedom Automobile) Response Parameters, Test Speed = 62 mph Sports Car Response Parameters Grand Prix Response Parameters	145 153 214 214 216
6.2 6.3	Comparison of Rectilinear and Rotational Dynamics Inertia, Damping, and Spring Coefficients US/OS Factor and Natural Frequency in Yaw	238 241 242 244
8.2 8.3 8.4 8.5	eq:model Data for beta of bet	304 305 306 310 320 336
1.1	Data and Data Reduction from Skid Pad Test	384
l2.2 l2.3	Principal Chassis Tuning Items Additional Principal Chassis Tuning Items Key to Primary Set-up Guide Key to Secondary Set-up Guide	389 390 392 402
l5.2 l5.3	Weight, Dimension, and Wing Data, G.S. 2G Flat Plate Drag by Two Different Methods Rotating Wheel Drag (Ref. 34) Wheel Aero Forces and Moments (Ref. 34)	499 565 570 570
16.2 16.3 16.4	Typical Roll Gradients, Based on Ref. 91 Effect of Installation Ratio with Different Spring Rates Data for Simplified Example Additional Data for Simplified Example—Roll Properties Suggested Numbers for Simplified Method	584 597 601 603 605
18.1	Wheel Load Summary	708

21.2	Recommended Maximum Stress Levels for Coil Springs	764
21.3	Maximum (Uncorrected) Stress Levels for Coil Springs	765
22.1	Indy Oval Track Car—Baseline Configuration	825
22.2	Non-Aerodynamic Version of Indy Oval Track Car	826
22.3	Indy Oval Track Car Damping Ratios	826