DIN 22102-3:2020-12 (E)

Conveyor belts with textile plies for bulk goods - Part 3: Permanent joints

Contents		Page
Foreword3		
1	Scope	4
2	Normative references	4
3	Terms, definitions and symbols	4
4 4.1	Dimensions, design and designation	
4.1 4.2	GeneralSplices for conveyor belts with one textile ply, for belt types 500/1	
4.2 4.3	Splices for conveyor belts with one textile ply, for belt types 500/1	
4.3	Splices for conveyor belts with two plies and intermediate tension member	
4.5	Splices for conveyor belts with two or more plies and bonding layers	
5 5.1	Splicing conveyor belts	
5.1 5.2	General Hot plates in vulcanizing machines	
6	Electrical and flammability safety requirements	12
7	Marking	12
Figures	Figure 1 Overlapping splice	5
Figure 2	2 Finger splice	6
Figure 3	3 Splice with intermediate tension member	7
Figure 4	I Stepped splice	8
Figure 5	5 Conveyor belt with two plies: 1-step splice	9
Figure 6	6 Conveyor belt with two plies: 2-step splice	9
Figure 7	7 Conveyor belt with three plies: 2-step splice	9
Figure 8	3 Conveyor belt with four plies: 3-step splice	10
Figure 9	9 Conveyor belt with five plies: 4-step splice	10
Tables 7	Table 1 Loss in breaking strength	5
Table 2	Minimum step lengths and splice lengths for overlapping splices	5
Table 3	Finger splice dimensions	6
Table 4	Minimum steps and splice lengths for splices with intermediate tension member	8
Table 5	Minimum steps and splice lengths for conveyor belts with two plies	11
Table 6	Minimum steps and splice lengths for conveyor belts with more than two plies	11