

DIN EN 16603-20-07:2022-12 (E)

Space engineering - Electromagnetic compatibility; English version EN 16603-20-07:2022

Contents	Page
European Foreword	7
Introduction	9
1 Scope	10
2 Normative references	11
3 Terms, definitions and abbreviated terms	12
3.1 Terms from other standards	12
3.2 Terms specific to the present standard	13
3.3 Abbreviated terms	15
4 Requirements	17
4.1 General system requirements	17
4.2 Detailed system requirements	17
4.2.1 Overview	17
4.2.2 EMC with the launch system	17
4.2.3 Lightning environment	18
4.2.4 Spacecraft charging and effects	18
4.2.5 Spacecraft DC magnetic emission	19
4.2.6 Radiofrequency compatibility	19
4.2.7 Hazards of electromagnetic radiation	20
4.2.8 Intrasystem EMC	20
4.2.9 EMC with ground equipment	20
4.2.10 Grounding	21
4.2.11 Electrical bonding requirements	21
4.2.12 Shielding (except wires and cables)	23
4.2.13 Wiring (including wires and cables shielding)	23
5 Verification	25
5.1 Overview	25
5.1.1 Introduction	25
5.1.2 Electromagnetic effects verification plan	25
5.1.3 Electromagnetic effects verification report	25

5.2	Test conditions	25
5.2.1	Measurement tolerances.....	25
5.2.2	Test site	26
5.2.3	Ground plane	28
5.2.4	Power source impedance.....	28
5.2.5	General test precautions	30
5.2.6	EUT test configurations.....	30
5.2.7	Operation of EUT	33
5.2.8	Use of measurement equipment	34
5.2.9	Emission testing.....	36
5.2.10	Susceptibility testing.....	37
5.2.11	Calibration of measuring equipment.....	39
5.2.12	Power bus voltage.....	40
5.2.13	Photographic data.....	40
5.3	System level	40
5.3.1	General.....	40
5.3.2	Safety margin demonstration for critical or EED circuits	40
5.3.3	EMC with the launch system	41
5.3.4	Lightning	41
5.3.5	Spacecraft and static charging	41
5.3.6	Spacecraft DC magnetic field emission	42
5.3.7	Intra–system electromagnetic compatibility	42
5.3.8	Radiofrequency compatibility	42
5.3.9	Grounding	42
5.3.10	Electrical bonding.....	42
5.3.11	Wiring and shielding.....	42
5.4	Equipment and subsystem level test procedures	43
5.4.1	Overview.....	43
5.4.2	CE, power leads, differential mode, 30 Hz to 100 kHz.....	43
5.4.3	CE, power and signal leads, 50 kHz to 100 MHz.....	45
5.4.4	CE, power leads, inrush current	48
5.4.5	DC Magnetic field emission, magnetic moment.....	51
5.4.6	RE, electric field, 30 MHz to 18 GHz	54
5.4.7	CS, power leads, 30 Hz to 100 kHz.....	58
5.4.8	CS, bulk cable injection, 50 kHz to 100 MHz	61
5.4.9	CS, power leads, transients	65
5.4.10	RS, magnetic field, 30 Hz to 100 kHz	69

5.4.11	RS, electric field, 30 MHz to 18 GHz	72
5.4.12	Susceptibility to wire-coupled electrostatic discharges (legacy method).....	79
5.4.13	Susceptibility to wire-coupled electrostatic discharges (current injection probe method).....	84
5.4.14	Susceptibility to electrostatic discharges into the chassis	87
5.4.15	CE, power leads, time domain	90
Annex A (informative) Subsystem and equipment limits.....	92	
A.1	Overview	92
A.2	CE on power leads, differential mode, 30 Hz to 100 MHz	92
A.3	CE on power leads, in-rush currents.....	94
A.4	CE on power and signal leads, common mode, 50 kHz to 100 MHz	94
A.5	<>deleted>>	95
A.6	DC magnetic field emission	95
A.6.1	General	95
A.6.2	Characterization.....	95
A.6.3	Limit	96
A.7	RE, low-frequency magnetic field.....	96
A.8	RE, low-frequency electric field.....	96
A.9	RE, electric field, 30 MHz to 18 GHz.....	97
A.10	CS, power leads, differential mode, 30 Hz to 100 kHz	97
A.11	CS, power and signal leads, common mode, 50 kHz to 100 MHz	98
A.12	CS, power leads, short spike transients	99
A.13	RS, magnetic field, 30 Hz to 100 kHz.....	100
A.14	RS, electric field, 30 MHz to 18 GHz.....	101
A.15	Susceptibility to wire-coupled electrostatic discharges (legacy method).....	102

Figures

Figure 4-1: Bonding requirements	22
Figure 5-1: RF absorber loading diagram	27
Figure 5-2: Line impedance stabilization network schematic	29
Figure 5-3: General test setup	31
Figure 5-4: Typical calibration fixture	35
Figure 5-5: Conducted emission, 30 Hz to 100 kHz, measurement system check	45
Figure 5-6: Conducted emission, 30 Hz to 100 kHz, measurement setup.....	45
Figure 5-7: Conducted emission, measurement system check	46
Figure 5-8: Conducted emission, measurement setup in differential mode	47

Figure 5-9: Conducted emission, measurement setup in common mode.....	47
Figure 5-10: Inrush current: measurement system check setup.....	49
Figure 5-11: Inrush current: measurement setup.....	49
Figure 5-12: Smooth deperm procedure.....	54
Figure 5-13: Electric field radiated emission. Basic test setup	56
Figure 5-14: Electric field radiated emission. Antenna positioning	56
Figure 5-15: Electric field radiated emission – Multiple antenna positions	57
Figure 5-16: CS, power leads, measurement system check set-up	59
Figure 5-17: CS, power leads, signal injection.....	60
Figure 5-18: Bulk cable injection, calibration set-up	64
Figure 5-19: Signal test waveform	64
Figure 5-20: CS, power and signal leads, bulk cable injection	65
Figure 5-21: CS, power leads, differential mode transients, calibration setup	66
Figure 5-22: CS, power leads, differential mode transients, injection setup	67
Figure 5-23: <>deleted>>	67
Figure 5-24: CS, power leads, common mode transients, calibration setup.....	67
Figure 5-25: CS, power leads, common mode transients, probe injection setup.....	68
Figure 5-26: Measurement system check configuration of the radiating system	70
Figure 5-27: Basic test setup	70
Figure 5-28: <>deleted>>	74
Figure 5-29: Example of electric field calibration test setup	75
Figure 5-30: RS Electric field – Multiple test antenna positions.....	76
Figure 5-31: <>deleted>>	76
Figure 5-32: Susceptibility to ESD: calibration configuration	81
Figure 5-33: Susceptibility to ESD: test equipment configuration.....	82
Figure 5-34: Example of compliant discharge current shape	83
Figure 5-35: Test setup for calibration of test waveform	85
Figure 5-36: Typical ESD pulse measured during calibration (3 A/div, 4 ns/div)	86
Figure 5-37: Wire-coupled ESD test setup (current injection probe method).....	86
Figure 5-38: Discharge current verification setup.....	89
Figure 5-39: Ideal contact discharge current waveform at 8 kV	89
Figure 5-40: Conducted emission, power leads, time domain: measurement setup.....	91
Figure A-1 : Power leads, differential mode conducted emission limit.....	93
Figure A-2 : Common mode conducted emission limit.....	95
Figure A-3 : Radiated electric field limit	97
Figure A-4 : Conducted susceptibility limit, frequency domain	98
Figure A-5 : Calibration level at the measurement port of the calibration fixture	99

Figure A-6 : CS, voltage spike in percentage of test bus voltage	100
Figure A-7 : Radiated susceptibility limit	101

Tables

Table 5-1: Absorption at normal incidence.....	27
Table 5-2: Bandwidth and measurement time	36
Table 5-3: Maximum step sizes for susceptibility tests.....	38
Table 5-4: Correspondence between test procedures and limits	43
Table A-1 : Equipment: susceptibility to conducted interference, test signal	99