

Edition 1.0 2015-09

INTERNATIONAL STANDARD



Universal serial bus interfaces for data and power – Part 2-2: Micro-USB Cables and Connectors Specification, Revision 1.01

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.220; 33.120; 35.200

ISBN 978-2-8322-2846-3

Warning! Make sure that you obtained this publication from an authorized distributor.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

Part 2-2: Micro-USB Cables and Connectors Specification, Revision 1.01

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62680-2-2 has been prepared by technical area 14: Interfaces and methods of measurement for personal computing equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on documents prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

This first edition cancels and replaces IEC 62680-2 published in 2013. This edition constitutes a technical revision.

The text of this standard is based on the following documents:

CDV	Report on voting	
100/2332/CDV	100/2435/RVC	

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all the parts in the IEC 62680 series, published under the general title *Universal serial* bus interfaces for data and power can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 62680 series is based on a series of specifications that were originally developed by the USB Implementers Forum (USB-IF). These specifications were submitted to the IEC under the auspices of a special agreement between the IEC and the USB-IF.

The USB Implementers Forum, Inc.(USB-IF) is a non-profit corporation founded by the group of companies that developed the Universal Serial Bus specification. The USB-IF was formed to provide a support organization and forum for the advancement and adoption of Universal Serial Bus technology. The Forum facilitates the development of high-quality compatible USB peripherals (devices), and promotes the benefits of USB and the quality of products that have passed compliance testing.

ANY USB SPECIFICATIONS ARE PROVIDED TO YOU "AS IS, "WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE USB IMPLEMENTERS FORUM AND THE AUTHORS OF ANY USB SPECIFICATIONS DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OR INFORMATION IN THIS SPECIFICAITON.

THE PROVISION OF ANY USB SPECIFICATIONS TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Entering into USB Adopters Agreements may, however, allow a signing company to participate in a reciprocal, royalty-free licensing arrangement for compliant products. For more information, please see:

http://www.usb.org/developers/docs/

http://www.usb.org/developers/devclass docs#approved

IEC DOES NOT TAKE ANY POSITION AS TO WHETHER IT IS ADVISABLE FOR YOU TO ENTER INTO ANY USB ADOPTERS AGREEMENTS OR TO PARTICIPATE IN THE USB IMPLEMENTERS FORUM."

This series covers the Universal Series Bus interfaces for data and power and consists of the following parts:

IEC 62680-1-1, Universal Serial Bus interfaces for data and power – Part 1-1: Common components – USB Battery Charging Specification, Revision 1.2

IEC 62680-2-1, Universal Serial Bus interfaces for data and power – Part 2-1: Universal Serial Bus Specification, Revision 2.0

IEC 62680-2-2, Universal Serial Bus interfaces for data and power – Part 2-2: USB Micro-USB Cables and Connectors Specification, Revision 1.01

IEC 62680-2-3, Universal Serial Bus interfaces for data and power – Part 2-3: Universal Serial Bus Cables and Connectors Class Document Revision 2.0

This part of the IEC 62680 series consists of several distinct parts:

 the main body of the text, which consists of the original specification and all ECN and Errata developed by the USB-IF.

CONTENTS

Ε(DREWC	JRD	2
IN	TRODU	JCTION	4
1	Intro	duction	10
	1.1	General	10
	1.2	Objective of the Specification	10
	1.3	Intended Audience/Scope	10
	1.4	Related Documents	10
2	Acro	onyms and Terms	10
3	Signi	ificant Features	11
	3.1	USB 2.0 Specification Compliance	11
	3.2 On-The-Go Device		12
	3.3 Connectors		12
	3.4	Compliant Cable Assemblies	12
	3.5	Plug Overmolds	12
4	Cabl	les and Connectors	13
	4.1	Introduction	13
	4.2	Micro-Connector Mating	
	4.3	Color Coding	
	4.4	Device, Cable and Adapter Delays	
	4.5	Compliant Usage of Connectors and Cables	
	4.5.1		
	4.5.2	2 Overmolds	15
	4.5.3		
	4.5.4	,	
	4.5.5	-	
	4.5.6	,	
	4.5.7	, 5	
	4.5.8		
	4.6	Drawings	
5	Elect	trical Compliance Requirements	
	5.1	Data Rates Beyond USB 2.0 (480 Mb/s>)	36
	5.2	Low Level Contact Resistance	
	5.3	Contact Current Rating	
	5.3.1	•	
	5.3.2 With Power Applied Contacts (1 and 5)		
6		hanical Compliance Requirements	
	6.1	Operating Temperature Range	
	6.1.1		
	6.1.2	·	
	6.2	Insertion Force	
	6.3	Extraction Force	
	6.4	Plating	
	6.4.1	•	
	6.4.2	·	
	6.5	Solderability	
		•	

	6.6	Peel Strength (Reference Only)	37
	6.7	Wrenching Strength (Reference Only)	37
	6.8	Lead Co-Planarity	37
	6.9	RoHS Compliance	
	6.10	Shell & Latch Materials	38
Fi	gure 4-1	I – Micro-A to Micro-B Cable	17
Fi	gure 4-2	2 – Standard-A to Micro-B Cable	18
Fi	gure 4-3	B – Micro-A to Captive Cable	19
Fi	gure 4-4	4 – Micro-A Plug Overmold, Straight	20
Fi	gure 4-5	5 – Micro-B Plug Overmold, Straight	21
Fi	gure 4-6	S – Micro-A Plug Interface	22
Fi	gure 4-7	7 – Micro-B Plug Interface	23
Fi	gure 4-8	B – Micro-A/B Plug Interface (Cut-section)	24
Fi	gure 4-9	9 – Micro-AB receptacle interface	25
Fi	gure 4-	I0 – Micro-B receptacle interface	26
Fi	gure 4-	11 – Micro-AB Receptacle Design	27
Fi	gure 4-	I2 – Micro-B Receptacle Design	28
Fi	gure 4-	I3 – Micro-A Plug Blockage	29
Fi	gure 4-	I4 – Micro-B Plug Blockage	30
Fi	gure 4-	15 – Micro-A Plug, Side Right Angle	31
Fi	gure 4-	16 – Micro-A Plug, Down Right Angle	32
Fi	gure 4-	I7 – Micro-B Plug, Side Right Angle	33
Fi	gure 4-	18 – Micro-B Plug, Down Right Angle	34
Fi	gure 4-	19 – Adapter, Standard-A receptacle to Micro-A plug	35
Fi	gure 4-9	9 – Micro-AB receptacle interface	40
Fi	gure 4-1	10 – Micro-B receptacle interface	41
Τá	able 4-1	- Plugs Accepted By Receptacles	13
		- Micro-A Plug Pin Assignments	
		Color Coding for Plugs and Receptacles	
		Maximum Delay for Micro-Connector and Cable	
		Maximum Delay for Standard Connector Cable	14

Note: All Engineering Change Notice's (ECN) and Errata documents as of September 01, 2012 that pertain to this core specification follow the last page of the specification starting on page 39.

Universal Serial Bus Micro-USB Cables and Connectors Specification

Revision 1.01 April 4, 2007

Revision History

Revision	Issue Date	Comment
0.6	1/30/2006	Revisions to all sections
0.7	3/24/2006	Added revised Micro-USB drawings to Rev.0.8
0.8	4/19/2006	Editorial changes and additions by Jan Fahllund (Nokia)
0.8b	4/26/2006	Corrections to the 0.8 version (based by comments from contributors)
0.9	6/7/2006	Corrections based on comments from the 0.8b version
1.0RC	8/2/2006	Added lubricant recommendation, LLRC delta change specified
1.01RC	11/10/2006	Editorial changes and addition based on Oct-06 USB-IF CCWG meeting.
1.02RC	12/10/2006	Shell material thickness tolerances changed so that material can be 0.25 mm or 0.3 mm; edited three pictures (Figure 4-10, 4-11 and 4-12).
1.03RC	12/11/2006	Two pictures edited (Figure 4-8 and 4-9). In fig 4-8 max height to be 2.8 mm MAX. In fig 4-9 R0.25 mm MAX to be R0.30 mm MAX.
1.0RC3	12/19/2006	For BoD approval
1.0	1/12/2007	Approved
1.0	1/22/2007	Cosmetic edits for publication
1.01	4/4/2007	Editorial corrections and additions to contributor list. Reinserted shell and plug material requirements as section 6.10, Clarified wording on Plating Recommendations.

Copyright @ 2006 USB Implementers Forum, Inc. (USB-IF). All rights reserved.

A LICENSE IS HEREBY GRANTED TO REPRODUCE THIS SPECIFICATION FOR INTERNAL USE ONLY. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, IS GRANTED OR INTENDED HEREBY.

USB-IF AND THE AUTHORS OF THIS SPECIFICATION EXPRESSLY DISCLAIM ALL LIABILITY FOR INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS, RELATING TO IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. USB-IF AND THE AUTHORS OF THIS SPECIFICATION ALSO DO NOT WARRANT OR REPRESENT THATSUCH IMPLEMENTATION(S) WILL NOT INFRINGE THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.

THIS SPECIFICATION IS PROVIDED "AS IS" AND WITH NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. ALL WARRANTIES ARE EXPRESSLY DISCLAIMED. NO WARRANTY OF MERCHANTABILITY, NO WARRANTY OF NON-INFRINGEMENT, NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, AND NOWARRANTY ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

IN NO EVENT WILL USB-IF OR USB-IF MEMBERS BE LIABLE TO ANOTHER FOR THE COST OF PROCURING SUBSTITUTE GOODS OR SERVICES, LOST PROFITS, LOSS OF USE, LOSS OF DATA OR ANY INCIDENTAL, CONSEQUENTIAL, INDIRECT, ORSPECIAL DAMAGES, WHETHER UNDER CONTRACT, TORT, WARRANTY, OR OTHERWISE, ARISING IN ANY WAY OUT OF THE USE OF THIS SPECIFICATION, WHETHER OR NOT SUCHPARTY HAD ADVANCE NOTICE OF THE POSSIBILITY OF SUCH DAMAGES.

All product names are trademarks, registered trademarks, or service marks of their respective owners.

Contributors

Mark Rodda, (editor) Motorola Jan Fahllund, (editor) Nokia

Jim Koser, (CCWG Chairman), Foxconn

Ed Beeman, 2010 Tech

Glen Chandler, Advanced-Connectek (Acon)

Charles Wang, Advanced-Connectek (Acon)

Toshinori Sasaki, Across Techno

Minoru Ohara, Allion Brad Brown, ATL

Christopher Mattson, ATL Marcus Darrington, ATL

Jaremy Flake, ATL Technology George Olear, Contech Research

Roy Ting, Elka Sophia Liu, ETC Bill Northey, FCI

Tsuneki Watanabe, Foxconn

Jim Zhao, Foxconn
David Ko, Foxconn
Jong Tseng, Foxconn
Jack Lu, Foxlink
Tim Chang, Foxlink
Sathid Inthon, Fujikura
Toshi Mimura, Fujijura

Alan Berkema, Hewlett-Packard

Karl Kwiat, Hirose Shinya Tono, Hirose Kazu Ichikawa, Hirose Ryozo Koyama, Hirose Yousuke Takeuchi, Hirose Tsuyoshi Kitagawa, Hosiden

Jim Eilers, Hosiden Kazuhiro Saito, JAE

Ron Muir, JAE

Mark Saubert, JAE Yasuhira Miya, JST Takahiro Diguchi, JST Yoichi Nakazawa, JST

Kevin Fang, Longwell Electronics Morgan Jair, Main Super Co.

Tom Kawaguchi, Matsushita Electric Works

Ron Ward, Matsushita Electric Works

Satoshi Yamamoto, Matsushita Electric Works

Yasuhiko Shinohara, Mitsumi Atsushi Nishio, Mitsumi Hitoshi Kawamura, Mitsumi Scott Sommers, Molex Kevin Delaney, Molex Kieran Wright, Molex

Sam Liu, Newnex Technology Corp.

Richard Petrie, Nokia Kai Silvennoinen, Nokia Panu Ylihaavisto, Nokia Arthur Zarnowitz, Palm Douglas Riemer, SMK Eric Yagi, SMK

Padraig McDaid, Molex

Mikko Poikselka, Molex

Abid Hussain, Summit Microelectronics

Kaz Osada, Tyco Masaru Ueno, Tyco Yoshikazu Hirata, Tyco Mark Paxson, VTM Inc.

UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

Part 2-2: Micro-USB Cables and Connectors Specification, Revision 1.01

1 Introduction

1.1 General

USB has become a popular interface for exchanging data between cell phone and portable devices. Many of these devices have become so small it is impossible to use standard USB components as defined in the USB 2.0 specification. In addition the durability requirements of the Cell Phone and Portable Devices market exceed the specifications of the current interconnects. Since Cell Phones and other small Portable Devices are the largest market potential for USB, this specification is addressing this very large market while meeting all the requirements for electrical performance within the USB 2.0 specification.

1.2 Objective of the Specification

The purpose of this document is to define the requirements and features of a Micro-USB connector that will meet the current and future needs of the Cell Phone and Portable Devices markets, while conforming to the USB 2.0 specification for performance, physical size and shape of the Micro-USB interconnect.

This is not a stand-alone document. Any aspects of USB that are not specifically changed by this specification are governed by the USB 2.0 Specification and USB On-The-Go Supplement.

1.3 Intended Audience/Scope

Cell phone and Portable Devices have become so thin that the current Mini-USB does not fit well within the constraints of future designs. Additional requirements for a more rugged connector that will have durability past 10 000 cycles and still meet the USB 2.0 specification for mechanical and electrical performance was also a consideration. The Mini-USB could not be modified and remain backward compatible to the existing connector as defined in the USB OTG specification.

1.4 Related Documents

USB 2.0

USB OTG Supplement